

Amendments to the Claims:

The following listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1.-32. (canceled)

33. (previously presented) A spool assembly for winding-up at least two adhesive carrier tapes of a packaging taped bag chain in an apparatus for taking up a succession of packaging bags, the spool assembly comprising at least two spools, each spool comprising a core with a core surface and walls forming a race where turns of tape are wound-up, wherein the core surface comprises resilient means for releasing a radial pressure acting on the turns of tape that have been wound up first.

34. (previously presented) The spool assembly according to claim 33, wherein the spool assembly comprises a differential gear unit positioned between said at least two spools, said differential gear unit being adapted to be, in use, removably connectable to a shaft of a bag loader whereby the at least two adhesive carrier tapes can be wound up on said spools with equal tension.

35. (previously presented) The spool assembly according to claim 34, wherein each of said spools has a recess in a surface which faces the other spool and wherein said differential gear unit is positioned in said recess.

36. (previously presented) The spool assembly according to claim 34, wherein each of said at least two spools is integrally formed with a bevel gear coaxial with said spool.

37. (currently amended) The spool assembly according to claim 36, wherein said differential gear unit comprises a core and at least one ~~satellite~~ pinion gear attached to said core and positioned to mesh with each bevel gear.

38. (previously presented) The spool assembly according to claim 37, wherein said differential gear unit core comprises a mating hole for mating with a shaft of a bag loader.

39. (currently amended) The spool assembly according to claim 34, wherein ~~it is~~ said at least two spools are contained in a housing, thus providing a cassette.

40. (previously presented) An apparatus for taking up a succession of imbricated packaging bags carried by at least two carrier tapes, said apparatus comprising at least two carrier tape winding spools positioned coaxially with one another; and a differential gear unit positioned between said spools, said differential gear unit being adapted to be, in use, removably connectable to a shaft of a bag loader whereby two carrier tapes can be wound up on said spools with equal tension, wherein the spools each comprise a core with a core surface and walls forming a race where turns of tape are wound-up, wherein the core surface comprises resilient means for releasing a radial pressure acting on the turns of tape that have been wound up first.

41. (previously presented) The apparatus according to claim 40, wherein each of said spools has a recess in a surface which faces the other spool and wherein said differential gear unit is positioned in said recesses.

42. (previously presented) The apparatus according to claim 40, wherein each of said spools is integrally formed with a bevel gear coaxial with said spool.

43. (currently amended) The apparatus according to claim 42, wherein said differential gear unit comprises a core and at least one ~~satellite~~ pinion gear attached to said core and positioned to mesh with each bevel gear.

44. (previously presented) The apparatus according to claim 43, wherein said differential gear unit core comprises a mating hole for mating with a shaft of a bag loader.

45. (previously presented) The apparatus according to claim 40, wherein said spools and differential gear unit are housed in a cassette.